

# MS-80 Pyranometer

Class A, Spectrally Flat & Fast Response



## Overview

Fast-Response and Spectrally Flat, with unprecedented low zero offset, analog output, and a 5-year recalibration interval, the MS-80 is an ISO 9060:2018 Class A leader and the IEC 61724-1 compliant go-to option for photovoltaic system performance monitoring and large weather monitoring sensor networks around the world.

The patented design of the MS-80, with its compact single-dome, guarantees unbeatable long-term stability thanks to the isolated thermopile detector, hermetically sealed under a pure Quartz diffusor. All solar wavelengths can pass through the diffusor, but the detector is protected from harmful levels of UV irradiance, a unique benefit that improves accuracy and reliability.

Our design, and commitment to quality, means that the MS-80 is better than competing pyranometers, best in class for accuracy, speed and reliability, whatever the application.

## Features



<0.5s Super-fast response time for always-accurate measurements, even during rapidly changing irradiance conditions



Unbeatable reliability, with a 5 Year warranty & recommended recalibration interval



<1W/m<sup>2</sup> record lowest zero offset A, and <0.5% lowest non-stability over 5-Years



Designed for IEC 61724-1 compliant photovoltaic system performance monitoring

## ISO Specifications

ISO 9060:2018 Parameters	CLASS A	MS-80
Response time 95%	<10s	<0.5s
Zero offset A - Thermal Radiation (200W/m <sup>2</sup> )	± 7W/m <sup>2</sup>	± 1W/m <sup>2</sup>
Zero offset B - Temperature change (5K/hr)	± 2W/m <sup>2</sup>	± 1W/m <sup>2</sup>
Zero offset C - Total zero off-set	± 10W/m <sup>2</sup>	± 2W/m <sup>2</sup>
Non-stability (change/year)	± 0.8%	< 0.5%/5 years
Non-linearity (100 to 1000W/m <sup>2</sup> )	± 0.5%	± 0.2%
Directional Response (at 1000W/m <sup>2</sup>   0 to 80°)	± 10W/m <sup>2</sup>	± 10W/m <sup>2</sup>
Spectral Error	± 0.5%	± 0.2%
Temperature Response (-20°C to 50°C)	± 1%	± 1%
Tilt Response (0-90°   1000W/m <sup>2</sup> )	± 0.5%	± 0.2%
Additional Signal Processing error	± 2W/m <sup>2</sup>	< 1 W/m <sup>2</sup>

## Accessories



### Solar Monitoring Station

Combine the class-leading MS-80 with EKO's ultra-accurate MS-57 pyrheliometer & the STR-Series automated sun tracker for second-to-none GHI, DHI & DNI measurements for PV site evaluation, performance monitoring, and cell optimisation.



### MS-Albedo Kit

The MS-Albedo kit can be used with any MS or S-Series EKO pyranometer, allowing two pyranometers to be deployed for albedo or reflected irradiance measurements for Bi-facial PV applications. The robust aluminium and stainless steel parts provide a reliable solution for easy, on-site assembly.



### MV-01

Achieve IEC 61724-1 compliance with the MV-01 ventilator and heater, an optional add-on that keeps the MS-80 free from dew, ice and snow. Proven in challenging environmental conditions, the MS-80 plus MV-01 is the go-to option globally for solar parks of all sizes, and large weather monitoring sensor networks.

## Applications



Designed for scientific research, industrial applications, and photovoltaic system performance monitoring, the patented design of the MS-80 assures best in class accuracy, speed and reliability whatever your application.

Built to last, with a 5-year warranty, 5-year recalibration interval, low-zero offset, and incredible stability, the MS-80 is ideal for utility-scale applications and other large-scale projects.



## Related Products



### S-Series Pyranometers

The IEC 61724-1 compliant and ISO 9060:2018 class-leading range of S-Series Pyranometers from EKO Instruments set a new standard in pyranometer performance and design, delivering unbeatable accuracy, reliability, and value.


The S-Series features onboard diagnostics, a 5-year warranty, 5-year recalibration interval, a unique 4-channel digital/analog interface, and superior electronic protection in every class, ideal for monitoring photovoltaic system performance, scientific research, meteorological applications, and more.

Explore EKO now, or get in touch to learn more about the Class A MS-80S, the Class B MS-60S and Class C MS-40S, the most accurate, reliable and robust family of pyranometers in the world.

## MS-80 Technical Features

Wavelength Range (nm)	285 to 3000
Irradiance range (W/m <sup>2</sup> )	0 to 4000
Operating temperature	-40 to 80°C
Supply voltage	5 - 30 VDC
Power Consumption	0 W
Ingress Protection	IP 67
Calibration traceability / uncertainty	ISO 17025 / WRR / < 0.7% (k = 1.96)
Standard Cable Length	10m (Optional lengths 20m, 30m, 50m)

## Technical Diagram



## QR

Use the QR code to visit our website, contact our team, or to find out more about the **MS-80**, other related products, and the full range of Class and industry-leading pyranometers from EKO.



## Explore EKO

Made in Japan for over 90 years, EKO solar energy sensors and environmental instruments are built on a legacy of innovation, an uncompromising commitment to quality, and industry-leading accuracy.

With a range of products and services to suit every project or application requirement, explore EKO now, or get in touch to find out how EKO Instruments can help you.



Albedometers



Pyranometers



Pyrheliometers



Spectro-Radiometers



Sky Imagers



DNI Sensors



Pyrgeometers



IV Measurement



Solar Monitoring Stations



Sun Trackers



Sensor Signal Converters



Heat Flux



UV Sensors



Temperature Sensors



Sky Scanners



Thermal Cond. Testers



PowerWise Systems, 124 Main Street, Bucksport, 04416 Maine, USA  
[www.powerwisesystems.com](http://www.powerwisesystems.com) +1 207 370 6517 [sales@powerwisesystems.com](mailto:sales@powerwisesystems.com)