



SiteSage ePod	
Communication Protocols	MiWi Wireless (802.15.4) 2.4GHz connection to Gateway RS485 link to Monitor expansion module (xPod)
Connections	15 CT sensor Ports 6 pin Monitor expansion module (xPod) connector (up to 3)
Power Requirements	Modular Power Connector (120V AC, 60Hz, 2.5W)
Environmental Specifications	Dimensions: 7"L x 2.5"W x 1.875"H Weight: 4 oz. Operating Temperature: -10° C to 60° C (14° F to 140° F) Humidity: 5% to 95%, non-condensing



SiteSage xPod	
Communication Protocols	MiWi Wireless (802.15.4) 2.4GHz connection to Gateway Expansion link to Energy Monitor
Connections	10 CT Sensor Ports Six-pin expansion module connector (up to 3) Connector (RS485/5V DC Power)
Environmental Specifications	Dimensions: 3.75"L x 1.875"W x .875"H Weight: 2 oz. Operating Temperature : -10° C to 60° C (14° F to 140° F) Humidity 5% to 95%, non-condensing



Current Transformers (CTs)			
Connections		2/4 Pin Molex Connector	
		0 - .333 VAC proportional to Current Reading	
Accuracy		Linearity: ±1% from 5% to 130% of rated primary current	
Physical	Capacity	Opening	Weight
	20A	10.2mm	1.5 oz
	50A	10.2mm	1.5 oz
	150A	25mm	2.3 oz
	300A	50mm x 80mm	2 lbs
	600A	50mm x 80mm	2 lbs
	1000A	80mm x 120mm	2.75 lbs
Operating Temperature : -15° C to 60° C (5° F to 140° F)			
Humidity: 5% to 95%, non-condensing			